

ESSENTIAL R5034

ACRYLIC POLYMER

Essential R5034 is a very hard, high Tg acrylic emulsion polymer that can be formulated into DTM formulations, as well as, stain resistant waterborne wood sealer. Formulations based on R5034 will give excellent salt spray resistance properties. Also, when formulated into a wood sealer it exhibits excellent resistance properties to coffee, iodine, mustard, tea and many other staining agents.

KEY BENEFITS

- High Tg Polymer
- Excellent Corrosion resistance
- Excellent stain resistance

DISCLAIMER: The information and recommendations contained herein are based on data believed to be correct. The information is offered solely for the customer's consideration, investigation and verification because of numerous factors beyond our control affecting the results of the use of products, Essential Industries, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for a particular purpose, other than that the product conforms to its applicable current standard specification. The manufacturer's only obligation shall be to replace such quantity of the product proven to be defective.

TYPICAL PROPERTIES*

Appearance	Milky-white emulsion
pH.....	8
Acid Number	25.9
Solids, % by weight	40%
Viscosity, cps @ 25C	< 100
Tg °C.....	73
Density, LBs/Gal	8.7
VOC Level (As Supplied)	
Lbs/Gal	0.0
g/L	0.0
Freeze/Thaw Stable	No
Konig Hardness (7days)	80

*These values should not be interpreted as specifications.



Essential[®] Polymers

The Spark of Innovation

Visit us on the web at
www.essentialpolymers.com

28391 Essential Road • P.O. Box 12
Merton, WI 53056-0012
(262) 538-0091 • FAX: (262) 538-1354