

ESSENTIAL R5861

CONCENTRATED FLOOR FINISH

R5861 is a 38% solids concentrated floor finish that when cut to 25% or less creates a finish with excellent gloss. It is ideal for areas where buffing is not required.

As a floor coating, R5861 is slip-resistant per ASTM Standard D2047.

KEY BENEFITS

- Good adhesion to a variety of substrates
- Compatible with many urethane dispersions
- Rapid dry
- Good clarity
- Non-yellowing

DISCLAIMER: The information and recommendations contained herein are based on data believed to be correct. The information is offered solely for the customer's consideration, investigation and verification because of numerous factors beyond our control affecting the results of the use of products, Essential Industries, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for a particular purpose, other than that the product conforms to its applicable current standard specification. The manufacturer's only obligation shall be to replace such quantity of the product proven to be defective.

TYPICAL PROPERTIES*

Appearance	Milky White
pH.....	8.5
Solids, % by Weight	37
Viscosity, cps @ 25°C	<50
Density, lbs/gal	8.8
% VOC	3.8
Freeze/Thaw Stability ...	Passes 3 cycles
Konig Hardness (secs).....	129

*These values should not be interpreted as specifications.



**Essential[®]
Polymers**

The Spark of Innovation

Visit us on the web at
www.essentialpolymers.com

28391 Essential Road • P.O. Box 12
Merton, WI 53056-0012
(262) 538-0091 • FAX: (262) 538-1354