

ECCOCRYL R5126

ACRYLIC EMULSION POLYMER

ECCOCRYL R5126 is a pure acrylic emulsion polymer with a high Tg. When formulated properly, the coatings will provide excellent exterior performance. The coatings will provide excellent adhesion to various substrates and provide water and stain resistance properties. R5126 has been formulated into pool and masonry coatings, as well as concrete sealers and primers.

KEY BENEFITS

- 100% acrylic
- Hardness
- Water resistance

DISCLAIMER: The information and recommendations contained herein are based on data believed to be correct. The information is offered solely for the customer's consideration, investigation and verification because of numerous factors beyond our control affecting the results of the use of products, Essential Industries, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for a particular purpose, other than that the product conforms to its applicable current standard specification. The manufacturer's only obligation shall be to replace such quantity of the product proven to be defective.

TYPICAL PROPERTIES*

Appearance	Translucent, white
pH.....	8.0
Solids, % by Weight	45
Viscosity, cps @ 25°C	< 200
Density, Lbs/gal	8.9
% VOC	0
Tg °C	49
Acid Number	16
Freeze/Thaw Stability	Passed
König Hardness (secs).....	104

*These values should not be interpreted as specifications.



The Spark of Innovation

Visit us on the web at
www.essentialpolymers.com

28391 Essential Road • P.O. Box 12
Merton, WI 53056-0012
(262) 538-0091 • FAX: (262) 538-1354